

powerful › compact

GOMMAIR 10



- › Industry leading compact, square design
- › Small footprint, no wheels
- › Electro-galvanized bodywork and structure with advanced painting procedure to grant an excellent preservation through time.

- › Easy Service design for maximum accessibility for ease of maintenance.
- › Easy managing with forklift.
- › Quiet and efficient Kubota Stage 3A engine.
- › Pressurized oil circuit to ensure efficient oil lubrication.
- › Air/oil separator filter, can guarantee an excellent air/oil separation.
- › Palletized, can be handled with forklift from all sides.

Technical Data

dimensions >

L = 1015 mm / 40.0"

W = 705 mm / 27.7"

H = 980 mm / 38.5"

weight >

265 kg / 584 lbs

GOMMAIR 10

DO YOU
KNOW

?

COMPRESSOR

Operating pressure	7 bar 100 psi
Free air delivery	1100 l/min 39 cfm

DIESEL ENGINE / ENVIRONMENTAL CONDITIONS

Engine make	KUBOTA
Engine type	Z 602
Emissions	Stage V / Tier 4
Displacement	599 cc
N. cylinders	2
Max engine power @3200 RPM	10,8 kW - 14,7 CV
Max engine speed	3200 RPM
Min engine speed	2400 RPM
Cooling system	Water
Fuel tank capacity	13 lt - 2.86 UK gal
Consumes	1,9 lt/h - 0.42 UK gal/h
Max ambient temperature	50°C - 122°F
Max altitude	1800 m a.s.l.
Min working temperature	-10°C / 14°F

...all our
ranges



also
available
AS...

customized
**SANDBLASTING
VERSION**

**INBUILT ADDITIONAL COOLER AND
SPECIFIC CONDENSATE SEPARATOR**

for cool and dry air

- › 1 compressor oil filter.
- › 1 single stage air filter for the compressor part of large size to ensure efficient filtering of air suctioned by the screw unit.
- › Spin-on engine and compressor oil filters for faster and easier maintenance.
- › 1 double stage air filter for the engine.
- › Protective device for engine cold start.
- › Combined radiator allowing both compressor oil cooling and engine liquid cooling.

ROTAR

