COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

Manufacturer: ELGi Model Number: EG 11V-125 X Air-cooled Water-cooled Full Load Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Efficiency Input Power (kW) 14.2 13.0 11.9	125 15 92.4 0.40 X 1 NA Capacity (acfm) ^{a,d} 62.0 56.0		1 psig b hp percent hp percent Specific Power kW/100 acfm) d	
Full Load Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Efficiency Input Power (kW) 14.2 13.0	125 15 92.4 0.40 X 1 NA Capacity (acfm) ^{a,d} 62.0	Type: # of Stages:	SCREW 1 psig b hp percent hp percent Specific Power kW/100 acfm) d	
Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Rating (if applicable) Fan Motor Nominal Efficiency Input Power (kW) 14.2 13.0	125 15 92.4 0.40 X 1 NA Capacity (acfm) ^{a,d} 62.0		psig ^b hp percent hp percent Specific Power kW/100 acfm) ^d	
Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Rating (if applicable) Fan Motor Nominal Efficiency Input Power (kW) 14.2 13.0	15 92.4 0.40 X 1 NA Capacity (acfm) ^{a,d} 62.0		hp percent hp percent Specific Power cW/100 acfm) ^d	
Drive Motor Nominal Efficiency Fan Motor Nominal Rating (if applicable) Fan Motor Nominal Efficiency Input Power (kW) 14.2 13.0	92.4 0.40 X 1 NA Capacity (acfm) ^{a,d} 62.0		percent hp percent Specific Power kW/100 acfm) ^d	
Fan Motor Nominal Rating (if applicable) Fan Motor Nominal Efficiency Input Power (kW) 14.2 13.0	0.40 X 1 NA Capacity (acfm) ^{a,d} 62.0		hp percent Specific Power kW/100 acfm) ^d	
Fan Motor Nominal Efficiency Input Power (kW) 14.2 13.0	NA Capacity (acfm) ^{a,d} 62.0		percent Specific Power kW/100 acfm) ^d	
14.2 13.0	Capacity (acfm) ^{a,d} 62.0		Specific Power xW/100 acfm) ^d	
13.0			22.00	
	56.0		22.99	
11.9		23.15		
	50.0	23.77		
9.9	39.0	25.43		
8.5	31.0	27.34		
7.3	23.0	31.89		
Total Package Input Power at Zero Flow c, d	0.00	kW		
Isentropic Efficiency	59.02	%		
40	50 75 Capacity(CFM)	100		
	Isentropic Efficiency 40 40 40 40 40 40 40 40 40 4	Isentropic Efficiency 59.02 September 15	Isentropic Efficiency 59.02 Sentropic Efficiency 59.02 Solution of the data in Section 8 Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW100acfm increments if necessary above 35	

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator bisite for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	±/- 10%
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data