			Rotary Compressor: Fixed 3 MODEL DATA - FOR COMPRE	-		٦
	1 Manufacturer: ELGi					-
		Model Number: EG 160W-100		Date:	06/29/2020	
	2	Air-cooled X Water-cooled			SCREW	
		Rated Capacity at Full Load Operating Pressure ^{a, e}		# of Stages:		
	3*			975	acfm ^{a,e}	_
	4*	Full Load Operating Pressu	d Operating Pressure ^b		psig ^b	
	5	Maximum Full Flow Opera	ating Pressure ^c	115	psig ^c	
	6	Drive Motor Nominal Rati		200	hp	_
		Drive Motor Nominal Effic	ciency		-	-
	7		-	96.2	percent	-
	8	Fan Motor Nominal Rating	g (if applicable)	0.39 X 1	hp	_
	9	Fan Motor Nominal Efficie	ency	NA	percent	
	10*	Total Package Input Power at Zero Flow ^e		49.52	kW ^e	
	11	Total Package Input Power	Package Input Power at Rated Capacity and Full Load ting Pressure ^d		kW^d	
	11	Operating Pressure ^d			K VV	
	12*	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		g	kW/100 cfm ^e	
				17.51		_
	13	Isentropic Efficiency		75.88	Percent	
*1	For mod	els that are tested in the CAGI Pe	erformance Verification Program, these items ar	re verified by the third party	administrator.	
	NOTES	 a. Measured at the discha ISO 1217, Annex C; A b. The operating pressure for this data sheet. c. Maximum pressure atta maximum pressure atta d. Total package input po e. Tolerance is specified 	pants in the third party verification program: rge terminal point of the compressor package in acc CFM is actual cubic feet per minute at inlet condition at which the Capacity (Item 3) and Electrical Cons ainable at full flow, usually the unload pressure sett inable before capacity control begins. May require wer at other than reported operating points will var in ISO 1217, Annex C, as shown in table below: wer" and "energy" are synonymous for purposes of	ons. umption (Item 11) were measu ing for load/no load control or additional power. y with control strategy.		
			Volume Flow Rate		Specific Energy	Ze
Member		m ³ /min	at specified conditions ft ³ / min	Volume Flow Rate	Consumption %]
		Below 0.5	Below 17.6	+/- 7	+/- 8	1
		0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+
30.1		1.5 to 15	53 to 529.7	+/- 5	+/- 6	