[Rotary Compressor: Fixed MODEL DATA - FOR COMPRE	-		٦
	1 Manufacturer: ELGi					
		Model Number: EG 160W-150		Date:	06/29/2020	
	2	Air-cooled X Water-cooled			SCREW	
		# of Stages:				
			a, e			_
	3*	Rated Capacity at Full Loa		778	acfm ^{a,e}	_
	4*	Full Load Operating Press	ure	150	psig ^b	
	5	Maximum Full Flow Oper	ating Pressure ^c	165	psig ^c	
		Drive Motor Nominal Rati			hp	
		Drive Motor Nominal Effi	ciency	200	-	-
	7			96.2	percent	_
	8	Fan Motor Nominal Rating		0.39 X 1	hp	_
	9	Fan Motor Nominal Effici	ency	NA	percent	
	10*	Total Package Input Power at Zero Flow ^e		48.62	kW ^e	
	11	Total Package Input Powe	ckage Input Power at Rated Capacity and Full Load		kW^d	
	11	Operating Pressure ^d		167.65	K VV	
	12*	Package Specific Power at Rated Capacity and Full Load Operatin		g	kW/100 cfm ^e	
		Pressure		21.55		_
	13	Isentropic Efficiency		76.76	Percent	
L	*For mod	els that are tested in the CAGI P	erformance Verification Program, these items a	re verified by the third party	administrator.	
TACKAR A IT A	Consult (NOTES	 a. Measured at the discht ISO 1217, Annex C; A b. The operating pressure for this data sheet. c. Maximum pressure att maximum pressure att d. Total package input point e. Tolerance is specified 	pants in the third party verification program: arge terminal point of the compressor package in act CFM is actual cubic feet per minute at inlet conditi e at which the Capacity (Item 3) and Electrical Cons ainable at full flow, usually the unload pressure sett ainable before capacity control begins. May require ower at other than reported operating points will var in ISO 1217, Annex C, as shown in table below: ower" and "energy" are synonymous for purposes of	ions. sumption (Item 11) were measu ting for load/no load control or 2 additional power. 9 with control strategy.		
	a monute		Volume Flow Rate		Specific Energy	Ze
			at specified conditions		Consumption]
Member		$\frac{\text{m}^3 / \text{min}}{\text{Below 0.5}}$	<u>ft³ / min</u> Below 17.6	<u>%</u> +/- 7	% +/- 8	_
		0.5 to 1.5	17.6 to 53	+/- /	+/- 8 +/- 7	
		1.5 to 15	53 to 529.7	+/- 5	+/- 6	+