_			Rotary Compressor: Fixed S	peed		
			MODEL DATA - FOR COMPRES	SED AIR		
	1	Manufacturer: ELGi				
	Model Number: EN 11-150			Date:	06/26/2020	
	2	X Air-cooled Water-cooled		Type:	SCREW	
				# of Stages:	1	
	3*	Rated Capacity at Full Los	ad Operating Pressure ^{a, e}	51.5	acfm ^{a,e}	
	4*	Full Load Operating Press		150	psig ^b	_
	5	Maximum Full Flow Oper		154	psig ^c	
F	6	Drive Motor Nominal Rating		154	hp	
-	7	Drive Motor Nominal Efficiency			1	_
-		Fan Motor Nominal Rating (if applicable)		91	percent	-
ŀ	8	Fan Motor Nominal Efficiency		0.375 x 1	hp	_
F	9			NA	percent	
⊢	10*	Total Package Input Power at Zero Flow ^e Total Package Input Power at Rated Capacity and Full Load		5.67	kW ^e	
	11	Operating Pressure ^d			kW ^d	
	12*	• 1	e Specific Power at Rated Capacity and Full Load Operating e ^e		kW/100 cfm ^e	
		Pressure ^e				
	13	Isentropic Efficiency		60.07	Percent	
*	For mode	l els that are tested in the CAGI P	erformance Verification Program, these items are	verified by the third party	administrator.	
CAC Dressed Air & Gas	NOTES:	 a. Measured at the disch ISO 1217, Annex C; 4 b. The operating pressur for this data sheet. c. Maximum pressure att maximum pressure att d. Total package input p e. Tolerance is specified 	pants in the third party verification program: arge terminal point of the compressor package in accord ACFM is actual cubic feet per minute at inlet condition e at which the Capacity (Item 3) and Electrical Consur- tainable at full flow, usually the unload pressure setting ainable before capacity control begins. May require a ower at other than reported operating points will vary of in ISO 1217, Annex C, as shown in table below: ower" and "energy" are synonymous for purposes of the	s. nption (Item 11) were measu g for load/no load control or dditional power. with control strategy.		
		Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Po
Member		<u>m³/min</u>	$\frac{ft^3}{min}$	%	%	9
		Below 0.5	Below 17.6	+/- 7	+/- 8	
		0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/-
030.1		1.5 to 15 Above 15	53 to 529.7 Above 529.7	+/- 5 +/- 4	+/- 6 +/- 5	