<b></b>			leral Uniform Test Method for Cert Rotary Compressor: Fixed S	peed	ι.	_
	MODEL DATA - FOR COMPRESSED AIR					
	1 Manufacturer: ELGi					
	Model Number: EN18-125			Date:	06/26/2020	
	2	X Air-cooled Water-cooled		Type:	SCREW	
				# of Stages:	1	
	3*	Rated Capacity at Full Loa	ad Operating Pressure <sup>a, e</sup>	99	acfm <sup>a,e</sup>	
	4*	Full Load Operating Press	Operating Pressure <sup>b</sup>		psig <sup>b</sup>	
		Maximum Full Flow Operating Pressure <sup>c</sup>		125	psig <sup>c</sup>	
		Drive Motor Nominal Rati			hp	
7 I		Drive Motor Nominal Efficiency Fan Motor Nominal Rating (if applicable)		25 92.80	percent hp	
	-	Fan Motor Nominal Effici	ency	0.35 x 2 NA 7.76	-	
	,	Total Package Input Powe	-		kW <sup>e</sup>	
	11	Total Package Input Powe	r at Rated Capacity and Full Load	1.10		
		Operating Pressure <sup>d</sup>		21.43	kW <sup>d</sup> kW/100 cfm <sup>e</sup>	
	10*	• •	Rated Capacity and Full Load Operating			
		Pressure <sup>e</sup>		21.75		
	13	Isentropic Efficiency		69.39	Percent	
			erformance Verification Program, these items are	, , ,	administrator.	
	NOTES:	<ul> <li>a. Measured at the discha ISO 1217, Annex C; A</li> <li>b. The operating pressure for this data sheet.</li> <li>c. Maximum pressure att maximum pressure att d. Total package input po- e. Tolerance is specified</li> </ul>	pants in the third party verification program: arge terminal point of the compressor package in accor (CFM is actual cubic feet per minute at inlet condition at which the Capacity (Item 3) and Electrical Consun ainable at full flow, usually the unload pressure setting ainable before capacity control begins. May require ac wer at other than reported operating points will vary w in ISO 1217, Annex C, as shown in table below: wer" and "energy" are synonymous for purposes of th	s. pption (Item 11) were measu g for load/no load control or lditional power. with control strategy.		
			Volume Flow Rate at specified conditions		Specific Energy Consumption	Zero F Pow
Member		<u>m<sup>3</sup>/min</u>	<u>ft<sup>3</sup> / min</u>	Volume Flow Rate %	%	%
		Below 0.5	Below 17.6	+/- 7	+/- 8	
		0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 1
		1.5 to 15 Above 15	53 to 529.7 Above 529.7	+/- 5 +/- 4	+/- 6 +/- 5	