Γ			Rotary Compressor: Fixed S MODEL DATA - FOR COMPRE	<u>^</u>		
	1 Manufacturer: ELGi					
	Model Number: EN5-100			Date:	06/26/2020	_
	2		X Air-cooled Water-cooled		SCREW	
				# of Stages:		
	3*	Rated Capacity at Full Lo	ad Operating Pressure ^{a, e}	29.9	acfm ^{a,e}	
	4*	Full Load Operating Press		100	psig ^b	
	-				psig	_
-	5	Maximum Full Flow Operating Pressure ^c Drive Motor Nominal Rating Drive Motor Nominal Efficiency		104		
_	6			8	hp	_
_	7		5	89.5	percent	_
	8		tor Nominal Rating (if applicable)		hp	_
_	9	Fan Motor Nominal Effici	-	NA	percent	
	10*	Total Package Input Power at Zero Flow ^e		2.77	kW ^e	
	11	Total Package Input Powe Operating Pressure ^d	ckage Input Power at Rated Capacity and Full Load		kW ^d kW/100 cfm ^e	
		Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e Isentropic Efficiency		6.91 5 23.11		
	12*					
	13			57.51	Percent	
С	onsult C NOTES:	 AGI website for a list of partic: a. Measured at the disch ISO 1217, Annex C; / b. The operating pressur for this data sheet. c. Maximum pressure at maximum pressure at d. Total package input p e. Tolerance is specified 	erformance Verification Program, these items ar pants in the third party verification program: arge terminal point of the compressor package in acc ACFM is actual cubic feet per minute at inlet conditi e at which the Capacity (Item 3) and Electrical Cons tainable at full flow, usually the unload pressure sett ainable before capacity control begins. May require ower at other than reported operating points will var- in ISO 1217, Annex C, as shown in table below: ower" and "energy" are synonymous for purposes of	<u>www.cagi.org</u> cordance with ons. umption (Item 11) were measu ing for load/no load control or additional power. y with control strategy.	red	
		Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Ze
Member		$\underline{m^3 / \min}$	ft^3 / min	%	%	1
		Below 0.5	Below 17.6	+/- 7	+/- 8	
		0.5 to 1.5 1.5 to 15	17.6 to 53 53 to 529.7	+/- 6 +/- 5	+/- 7 +/- 6	+,
30.1		1.5 to 15 Above 15	Above 529.7	+/- 5 +/- 4	+/- 6 +/- 5	