

## COMPRESSOR DATA SHEET

**Federal Uniform Test Method for Certain Air Compressors Not Applicable**

**Rotary Compressor: Variable Frequency Drive**

| MODEL DATA - FOR COMPRESSED AIR |   |  |   |
|---------------------------------|---|--|---|
| 1                               | Manufacturer: <b>ELGi</b>   |  |   |
| 2                               | Model Number: <b>OF300V-115</b>   |  | Date: <b>06/26/2020</b>                   |
|                                 | <input type="checkbox"/> Air-cooled   | <input checked="" type="checkbox"/> Water-cooled | Type: <b>SCREW</b>                        |
|                                 | <input type="checkbox"/> Lubricated   | <input checked="" type="checkbox"/> Oil Free     | # of Stages: <b>2</b>                     |
| 3*                              | Full Load Operating Pressure <sup>b</sup>   | <b>115</b>                                       | psig <sup>b</sup>                         |
| 4                               | Drive Motor Nominal Rating  | <b>400</b>                                       | hp  |
| 5                               | Drive Motor Nominal Efficiency  | <b>96.2</b>                                      | percent                                   |
| 6                               | Fan Motor Nominal Rating (if applicable)  | <b>NA</b>  | hp  |
| 7                               | Fan Motor Nominal Efficiency  | <b>NA</b>  | percent                                   |
| 8*                              | Input Power (kW)  | Capacity (acfm) <sup>a,d</sup>                   | Specific Power (kW/100 acfm) <sup>d</sup> |
|                                 | <b>312.5</b>  | <b>1680.0</b>                                    | <b>18.60</b>                              |
|                                 | <b>283.8</b>  | <b>1496.0</b>                                    | <b>18.97</b>                              |
|                                 | <b>269.8</b>  | <b>1418.0</b>                                    | <b>19.03</b>                              |
|                                 | <b>242.9</b>  | <b>1267.0</b>                                    | <b>19.17</b>                              |
|                                 | <b>228.9</b>  | <b>1193.0</b>                                    | <b>19.18</b>                              |
| <b>203.0</b>                    | <b>1050.0</b>   | <b>19.33</b>                                     |   |
| 9*                              | Total Package Input Power at Zero Flow <sup>c, d</sup>  | <b>0.00</b>                                      | kW  |
| 10                              | <p style="text-align: center; font-size: small;">                     Note: Graph is only a visual representation of the data in Section 8<br/>                     Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35<br/>                     X-Axis Scale, 0 to 25% over maximum capacity                 </p> |  |   |

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: [www.cagi.org](http://www.cagi.org)



Member

- NOTES:
- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
  - b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
  - c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
  - d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:  
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

| Volume Flow Rate at specified conditions |                       | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|-----------------------|------------------|-----------------------------|---------------------------|
| m <sup>3</sup> / min                     | ft <sup>3</sup> / min | %                | %                           | %                         |
| Below 0.5                                | Below 17.6            | +/- 7            | +/- 8                       |                           |
| 0.5 to 1.5                               | 17.6 to 53            | +/- 6            | +/- 7                       |                           |
| 1.5 to 15                                | 53 to 529.7           | +/- 5            | +/- 6                       | +/- 10%                   |
| Above 15                                 | Above 529.7           | +/- 4            | +/- 5                       |                           |

ROT 031.2

12/19 R3

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.