


COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

| MODEL DATA - FOR COMPRESSED AIR | | | |
|---------------------------------|---|--|--|
| 1 | Manufacturer: ELGi | | |
| 2 | Model Number: OF90V-100 | | Date: 06/26/2020 |
| | <input type="checkbox"/> Air-cooled | <input checked="" type="checkbox"/> Water-cooled | Type: SCREW |
| | <input type="checkbox"/> Lubricated | <input checked="" type="checkbox"/> Oil Free | # of Stages: 2 |
| 3* | Full Load Operating Pressure ^b | 100 | psig ^b |
| 4 | Drive Motor Nominal Rating | 150 | hp |
| 5 | Drive Motor Nominal Efficiency | 95 | percent |
| 6 | Fan Motor Nominal Rating (if applicable) | NA | hp |
| 7 | Fan Motor Nominal Efficiency | NA | percent |
| 8* | Input Power (kW) | Capacity (acfm) ^{a,d} | Specific Power (kW/100 acfm) ^d |
| | 110.3 | 549.0 | 20.10 |
| | 104.7 | 511.0 | 20.49 |
| | 99.2 | 486.0 | 20.42 |
| | 93.9 | 461.0 | 20.36 |
| | 89.6 | 438.0 | 20.45 |
| 81.0 | 396.0 | 20.45 | |
| 9* | Total Package Input Power at Zero Flow ^{c, d} | 0.00 | kW |
| 10 |  <p style="font-size: small; text-align: center;"> Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity </p> | | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



Member

- NOTES:
- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
 - b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
 - c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
 - d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

| Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power |
|--|-----------------------|------------------|-----------------------------|---------------------------|
| m ³ / min | ft ³ / min | % | % | % |
| Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | |
| 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | |
| 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | +/- 10% |
| Above 15 | Above 529.7 | +/- 4 | +/- 5 | |

ROT 031.2