## **COMPRESSOR DATA SHEET**



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

| MODEL DATA - FOR COMPRESSED AIR |   |   |   |            |  |  |  |
|---------------------------------|---|---|---|------------|--|--|--|
| 1                               | Manufacturer: <b>ELGi</b>                               |   |   |            |  |  |  |
|                                 | Model Number: <b>OF110V-100</b>                         |   | Date:                                     | 03/01/2023 |  |  |  |
| 2                               | Air-cooled X Water-cooled                               |   | Type:                                     | SCREW      |  |  |  |
|                                 | Lubricated X Oil Free                                   |   | # of Stages: 2                            |            |  |  |  |
| 3*                              | Full Load Operating Pressure b                          | 100   | psig                                      |            |  |  |  |
| 4                               | Drive Motor Nominal Rating                              | 150   | hp  |            |  |  |  |
| 5                               | Drive Motor Nominal Efficiency                          | 95  | percent                                   |            |  |  |  |
| 6                               | Fan Motor Nominal Rating (if applicable)                |   | hp  |            |  |  |  |
| 7                               | Fan Motor Nominal Efficiency                            | NA  | percent                                   |            |  |  |  |
| 8*                              | Input Power (kW)  | Capacity (acfm) <sup>a,d</sup>  | Specific Power (kW/100 acfm) <sup>d</sup> |            |  |  |  |
|                                 | 135.6   | 678.0   | 20.00                                     |            |  |  |  |
|                                 | 123.2   | 621.0   | 19.83                                     |            |  |  |  |
| 0.                              | 108.7   | 555.0   | 19.58                                     |            |  |  |  |
|                                 | 94.7  | 475.0   | 19.94                                     |            |  |  |  |
|                                 | 85.9  | 424.0   | 20.26                                     |            |  |  |  |
|                                 | 72.2  | 350.0   | 20.61                                     |            |  |  |  |
| 9*                              | Total Package Input Power at Zero Flow c, d             | 0.00  | kW  |            |  |  |  |
| 10                              | Note: Graph is only a v<br>Note: Y-Axis Scale, 10 to 35 | 375 500  Capacity(CFM)  risual representation of the data in , + 5kW/100acfm increments if neces , 0 to 25% over maximum capacity |   |            |  |  |  |

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
   ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

| Volume Flow Rate at specified conditions |                       | Volume Flow Rate | Specific Energy<br>Consumption | No Load /<br>Zero Flow<br>Power |  |
|--|-----------------------|------------------|--------------------------------|---------------------------------|--|
| m <sup>3</sup> / min                     | ft <sup>3</sup> / min | %                | %                              | %                               |  |
| Below 0.5                                | Below 17.6            | +/- 7            | +/- 8                          |                                 |  |
| 0.5 to 1.5                               | 17.6 to 53            | +/- 6            | +/- 7                          | 1/ 100/                         |  |
| 1.5 to 15                                | 53 to 529.7           | +/- 5            | +/- 6                          | +/- 10%                         |  |
| Above 15                                 | Above 529.7           | +/- 4            | +/- 5                          |                                 |  |

ROT 031.2