## COMPRESSOR DATA SHEET



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

## **Rotary Compressor: Variable Frequency Drive**

|                                      |                      |  |   | ariable Frequency  |                                 |   |  |
|--------------------------------------|----------------------|--|---|--|---------------------------------|---|--|
|                                      | 1 Manufac            | turer: ELGi  |   |  |                                 |   |  |
|                                      | Model N              | Model Number: OF132V-100   |   |  | Date:                           | Date: 03/01/2023                                  |  |
|                                      | 2                    | Air-cooled   | X Water-cooled  |  | Type:                           | SCREW   |  |
|                                      |                      | -  |   |  | s: Not Applicable               |   |  |
|                                      | 3* Full Loa          | d Operating Press  | X Oil Free  | 100  | # of Stages:                    | psig <sup>b</sup>                                 |  |
|                                      |                      | Drive Motor Nominal Rating   |   | 100<br>200   |                                 | hp  |  |
|                                      |                      | Drive Motor Nominal Efficiency<br>Fan Motor Nominal Rating (if applicable)   |   | 95.4   |                                 | percent<br>hp                                     |  |
|                                      |                      |  |   | 95.4   |                                 |   |  |
|                                      |                      | Fan Motor Nominal Efficiency   |   | NA   |                                 | percent   |  |
|                                      |                      | Input Powe   |   | Capacity (acfm) <sup>a,d</sup>   |                                 | Specific Power<br>(kW/100 acfm) <sup>d</sup>      |  |
|                                      |                      | 170.8  | 863.0   | 19.79  |                                 |   |  |
|                                      |                      | 148.6  |   | 761.0  |                                 | 19.79   |  |
| 8                                    | 8*                   | 133.7  | 692.0   |  | 19.31                           |   |  |
|                                      |                      | 117.1  | 604.0   |  | 19.38                           |   |  |
|                                      |                      | 102.1  | 518.0   |  | 19.71                           |   |  |
|                                      |                      | 71.0   |   |  | 20.28                           |   |  |
|                                      | 9* Total Pa          | Total Package Input Power at Zero Flow <sup>c, d</sup>   |   | 0.00   |                                 | kW  |  |
| :                                    | 10                   | - 0 5<br>Specific Power(kW/100CFW)<br>Specific Power(kW/100CFW)<br>- 0 1<br>- 0 1  | C<br>Note: Graph is only a vi   | 525 700<br>apacity(CFM)<br>sual representation of the data in<br>+ 5kW/100acfm increments if nece                          |                                 |   |  |
|                                      |                      |  |   | 0 to 25% over maximum capacity<br>gram, these items are verification program.  | ied by the third                |   |  |
| CAGE<br>Compressed Air & Gas Institu | OTES: a<br>b<br>c    | Measured at the disch<br>ACFM is actual cubic<br>The operating pressur<br>No Load Power. In au<br>manufacturer may sta<br>Tolerance is specified | arge terminal point of the cc<br>c feet per minute at inlet com<br>re at which the Capacity (Iter<br>ccordance with ISO 1217, A<br>te "not significant" or "0" or<br>l in ISO 1217, Annex E, as s | mpressor package in accorda<br>litions.<br>n 8) and Electrical Consump<br>nnex E, if measurement of no<br>the test report. | tion (Item 8) we                | 217, Annex E;<br>re measured for this data sheet. |  |
| Member                               | Volume               | Volume Flow Rate at specified Volum conditions   |   | Specific Energy<br>Consumption   | No Load /<br>Zero Flow<br>Power |   |  |
|                                      | m <sup>3</sup> / min | $ft^3 / min$   | %   | %  | Power<br>%                      |   |  |
|                                      | Below 0.5            | Below 17.6   | +/- 7   | +/- 8  |                                 |   |  |
|                                      | 0.5 to 1.5           | 17.6 to 53   | +/- 6   | +/- 7  | +/- 10%                         |   |  |
|                                      |                      |  |   | 1  | ±/- 10%                         | 1   |  |
|                                      | 1.5 to 15            | 53 to 529.7  | +/- 5   | +/- 6  |                                 |   |  |

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.

12/19 R3