COMPRESSOR DATA SHEET



Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

| MODEL DATA - FOR COMPRESSED AIR | | | | | | | |
|---------------------------------|--|---|-------------------|---|--|--|--|
| 1 | Manufacturer: ELGi | | | | | | |
| | Model Number: OF132V-145 | | Date: | 03/01/2023 | | | |
| 2 | Air-cooled X Water-cool | | | SCREW | | | |
| | Lubricated X Oil Free # of | | | <u> 2</u> | | | |
| 3* | Full Load Operating Pressure | 145 | psig ^b | | | | |
| 4 | Drive Motor Nominal Rating | 200 | hp | | | | |
| 5 | Drive Motor Nominal Efficiency | 95.4 | percent | | | | |
| 6 | Fan Motor Nominal Rating (if applicable) | | hp | | | | |
| 7 | Fan Motor Nominal Efficiency | NA | percent | | | | |
| 8* | Input Power (kW) | Capacity (acfm) ^{a,d} | | Specific Power (kW/100 acfm) ^d | | | |
| | 160.9 | 700.0 | 22.9 | 98 | | | |
| | 156.9 | 683.0 | 22.9 | 98 | | | |
| | 153.0 | 664.0 | 23.0 | 04 | | | |
| | 148.1 | 642.0 | 23.0 | 08 | | | |
| | 143.5 | 619.0 | 23.1 | 17 | | | |
| | 138.8 | 597.0 | 23.2 | 26 | | | |
| 9* | Total Package Input Power at Zero Flow | c, d 0.00 | kW | | | | |
| 10 | Note: Y-Axis Scal | 300 450 600 Capacity(CFM) is only a visual representation of the data in e, 10 to 35, + 5kW/100acfm increments if neces Axis Scale, 0 to 25% over maximum capacity | Section 8 | | | | |

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

| Volume Flow Rate at specified conditions | | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Flow Power | |
|--|-----------------------|------------------|--------------------------------|---------------------------------|--|
| m³/min | ft ³ / min | % | % | % | |
| Below 0.5 | Below 17.6 | +/- 7 | +/- 8 | | |
| 0.5 to 1.5 | 17.6 to 53 | +/- 6 | +/- 7 | . / 100/ | |
| 1.5 to 15 | 53 to 529.7 | +/- 5 | +/- 6 | +/- 10% | |
| Above 15 | Above 529.7 | +/- 4 | +/- 5 | | |

ROT 031.2

12/19 R3