COMPRESSOR DATA SHEET



Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR						
Manufacturer: ELGi						
Model Number: OF132AV-125			10/18/2023			
X Air-cooled Water-cooled			SCREW			
Lubricated X Oil Free			2			
Full Load Operating Pressure b	125	psig b				
Drive Motor Nominal Rating	200	hp				
Drive Motor Nominal Efficiency	95.4	percent				
Fan Motor Nominal Rating (if applicable)	3.9 x 2	hp				
Fan Motor Nominal Efficiency	NA	percent				
Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power				
			(kW/100 acfm) ^d			
		20.	kW			
35 (W) 30	isual representation of the data in + 5kW/100acfm increments if neces					
	Manufacturer: ELGi Model Number: OF132AV-125 X Air-cooled Water-cooled Lubricated X Oil Free Full Load Operating Pressure Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Efficiency Input Power (kW) 165.2 150.3 142.7 132.5 115.7 95.2 Total Package Input Power at Zero Flow c, d Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Graph is only a v Note: Y-Axis Scale, 10 to 35, Note: Y-A	Manufacturer: ELGi Model Number: OF132AV-125 X Air-cooled Water-cooled Lubricated X Oil Free Full Load Operating Pressure 200 Drive Motor Nominal Rating 200 Drive Motor Nominal Efficiency 95.4 Fan Motor Nominal Efficiency 95.4 Fan Motor Nominal Efficiency NA Input Power (kW) Capacity (acfm) a.d 165.2 765.0 150.3 664.0 142.7 614.0 132.5 563.0 115.7 461.0 95.2 360.0 Total Package Input Power at Zero Flow c, d Note: Graph is only a visual representation of the data in Note: Y-Axis Scale, 10 to 35, -5 kW/100acfm increments if necessarian shorts.	Manufacturer: ELGi			

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m³/min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	1/ 100/
1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2

12/19 R3