## **COMPRESSOR DATA SHEET**



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

| MODEL DATA - FOR COMPRESSED AIR |  |  |   |            |  |  |  |
|---------------------------------|--|--|---|------------|--|--|--|
| 1                               | Manufacturer: <b>ELGi</b>  |  |   |            |  |  |  |
|                                 | Model Number: OF145AV-115  |  | Date:                                     | 10/18/2023 |  |  |  |
| 2                               | X Air-cooled Water-coo   | led  | Type:                                     | SCREW      |  |  |  |
|                                 | Lubricated X Oil Free  |  | # of Stages: 2                            |            |  |  |  |
| 3*                              | Full Load Operating Pressure   | 115  | psig b                                    |            |  |  |  |
| 4                               | Drive Motor Nominal Rating   | 200  | hp  |            |  |  |  |
| 5                               | Drive Motor Nominal Efficiency   | 95.4   | percent                                   |            |  |  |  |
| 6                               | Fan Motor Nominal Rating (if applicable  | 3.9 x 2  | hp  |            |  |  |  |
| 7                               | Fan Motor Nominal Efficiency   | NA   | percent                                   |            |  |  |  |
| 8*                              | Input Power (kW)   | Capacity (acfm) <sup>a,d</sup>   | Specific Power (kW/100 acfm) <sup>d</sup> |            |  |  |  |
|                                 | 180.8  | 873.0  | 20.7                                      |            |  |  |  |
|                                 | 165.7  | 779.0  | 21.2                                      | 28         |  |  |  |
| 8"                              | 158.0  | 732.0  | 21.5                                      | 59         |  |  |  |
|                                 | 149.1  | 685.0  | 21.78                                     |            |  |  |  |
|                                 | 137.9  | 617.0  | 22.3                                      | 34         |  |  |  |
|                                 | 125.6  | 550.0  | 22.85                                     |            |  |  |  |
| 9*                              | Total Package Input Power at Zero Flow   | c, d <b>0.00</b>   | kW  |            |  |  |  |
| 10                              | 35<br>(N) 30<br>25<br>20<br>20<br>20<br>15<br>0 175<br>Note: Graph<br>Note: Y-Axis Sea | 350 525 700 Capacity(CFM)  is only a visual representation of the data in le, 10 to 35, + 5kW/100acfm increments if neces Axis Scale, 0 to 25% over maximum capacity |   |            |  |  |  |

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
   ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

| Volume Flow Rate at specified conditions |                       | Volume Flow Rate | Specific Energy<br>Consumption | No Load /<br>Zero Flow<br>Power |  |
|--|-----------------------|------------------|--------------------------------|---------------------------------|--|
| m <sup>3</sup> / min                     | ft <sup>3</sup> / min | %                | %                              | %                               |  |
| Below 0.5                                | Below 17.6            | +/- 7            | +/- 8                          |                                 |  |
| 0.5 to 1.5                               | 17.6 to 53            | +/- 6            | +/- 7                          | +/- 10%                         |  |
| 1.5 to 15                                | 53 to 529.7           | +/- 5            | +/- 6                          |                                 |  |
| Above 15                                 | Above 529.7           | +/- 4            | +/- 5                          |                                 |  |

ROT 031.2

<sup>\*</sup>For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>