COMPRESSOR DATA SHEET



Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: ELGi						
	Model Number: OF145AV-145		Date:	10/18/2023			
2	X Air-cooled Water-cooled		Type:	SCREW			
	Lubricated X Oil Free		# of Stages: 2				
3*	Full Load Operating Pressure b	145 psig ^b					
4	Drive Motor Nominal Rating	200	hp				
5	Drive Motor Nominal Efficiency	95.4	percent				
6	Fan Motor Nominal Rating (if applicable)	3.9 x 2	hp				
7	Fan Motor Nominal Efficiency	NA	percent				
8*	Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power				
				(kW/100 acfm) ^d			
	173.2	714.0	24.				
	169.5	690.0	24.				
	167.5	677.0	24.				
	165.6	665.0	24.9				
	155.7	608.0	25.0				
o.t.		145.0 550.0		37			
9*	Total Package Input Power at Zero Flow c, d 0.00			kW			
10	Note: Graph is only a v Note: Y-Axis Scale, 10 to 35	0 450 600 Capacity(CFM) isual representation of the data in + \$kW/100acfm increments if neces 0 to 25% over maximum capacity					

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power	
m³/min	ft ³ / min	%	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8		
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	. / 100/	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%	
Above 15	Above 529.7	+/- 4	+/- 5		

ROT 031.2

12/19 R3