## COMPRESSOR DATA SHEET



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

	MODEL DA	TA - FOR COMPRESS	ED AIR		
1	Manufacturer: <b>ELGi</b>				
	Model Number: <b>OF90AV-100</b>		Date:	10/03/2023	
2	X Air-cooled Water-co	poled	Type:	SCREW	
	Lubricated X Oil Free	vil Free # of Stages: 2		2	
3*	Full Load Operating Pressure	100		psig	
4	Drive Motor Nominal Rating	125		hp	
5	Drive Motor Nominal Efficiency	95		percent	
6	Fan Motor Nominal Rating (if applicab	le) <b>2.1 x 2</b>		hp	
7	Fan Motor Nominal Efficiency	NA		percent	
	Input Power (kW)	Capacity (acfm)	a,d	Specific Power (kW/100 acfm) <sup>d</sup>	
	117.6	568.0	20.		
0.4	104.5	493.0	21.		
8*	97.8	456.0	21.	46	
	90.3	418.0	21.	58	
	85.3	389.0	21.	92	
	80.0	360.0	22.	23	
9*	Total Package Input Power at Zero Flow	w <sup>c, d</sup> <b>0.00</b>		kW	
10		250 375 Capacity(CFM)  aph is only a visual representation of the ds			

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m³/min	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	1/ 100/
1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2