## COMPRESSOR DATA SHEET



## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

MODEL DATA - FOR COMPRESSED AIR								
1	Manufacturer: <b>ELGi</b>							
	Model Number: <b>OF90AV-125</b>		Date: <b>08/17/2023</b>					
2	X Air-cooled Water-cooled		Type: <b>SCREW</b>					
	Lubricated X Oil Free		# of Stages: 2					
3*	Full Load Operating Pressure b	125 psig <sup>b</sup>						
4	Drive Motor Nominal Rating	125	hp					
5	Drive Motor Nominal Efficiency	95	percent					
6	Fan Motor Nominal Rating (if applicable)	2.1 x 2	hp					
7	Fan Motor Nominal Efficiency	NA	percent					
	Input Power (kW)	Capacity (acfm) <sup>a,d</sup>	Specific Power					
8*			(kW/100 acfm) <sup>d</sup>					
	119.0	502.0	23.70					
	111.5	452.0	24.64					
	107.5 102.3	428.0	25.14 25.40					
	99.5	381.0	26.09					
	96.1	360.0	26.70					
9*	Total Package Input Power at Zero Flow c, d	0.00	20.70 kW					
,	Total Fackage input Fower at Zero Flow	0.00	KW					
	35 W							
	Specific Power(kW/100CFM)  12  12							
	χ. 25							
10	§ 20 -							
	)							
	0 125	250 375 apacity(CFM)	500					
	Note: Graph is only a visual representation of the data in Section 8  Note: Y-Axis Scale, 10 to 35, +5kW/100acfm increments if necessary above 35  X-Axis Scale, 0 to 25% over maximum capacity							

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m³/min	ft <sup>3</sup> / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	1/ 100/
1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/- 10%
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2