F			Rotary Compressor: Fixed S	<u>^</u>		_
	MODEL DATA - FOR COMPRESSED AIR					
	1 Manufacturer: ELGi					
	Model Number: EG 75-125		5-125	Date:	12/20/2022	
	2	X Air-cooled Water-cooled		Type:	SCREW	
				# of Stages:	1	
ſ	3*	Rated Capacity at Full Loa	ad Operating Pressure ^{a, e}	458	acfm ^{a,e}	
Ī	4*	Full Load Operating Press	ure ^b	125 140 100	psig ^b psig ^c hp	
Ī	5	Maximum Full Flow Oper				
Ī	6	Drive Motor Nominal Rat				
ľ	7	Drive Motor Nominal Efficiency		95.4	percent	
8		Fan Motor Nominal Rating (if applicable)		2.07(1.55)- (460V)	1	
ŀ	9	Fan Motor Nominal Efficiency			percent	
ŀ	10*	Total Package Input Power at Zero Flow ^e		NA 22.50	kW ^e	
-	11		otal Package Input Power at Rated Capacity and Full Load berating Pressure ^d ckage Specific Power at Rated Capacity and Full Load Operating		kW ^d kW/100 cfm ^e	
-	11	Operating Pressure ^d				
	12*	Package Specific Power at Pressure ^e				
ŀ		Isentropic Efficiency		18.25		-
	13			82.30	Percent	
	Consult (NOTES	 CAGI website for a list of partici a. Measured at the disch ISO 1217, Annex C: A b. The operating pressure for this data sheet. c. Maximum pressure att maximum pressure att d. Total package input po e. Tolerance is specified 	erformance Verification Program, these items are pants in the third party verification program: arge terminal point of the compressor package in acco CCFM is actual cubic feet per minute at inlet condition e at which the Capacity (Item 3) and Electrical Consu ainable at full flow, usually the unload pressure settir ainable before capacity control begins. May require a over at other than reported operating points will vary in ISO 1217, Annex C, as shown in table below: over" and "energy" are synonymous for purposes of the	<u>www.cagi.org</u> rdance with ns. mption (Item 11) were measu ng for load/no load control or idditional power. with control strategy.	red	
Concession of the second		Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Ze
Member		<u>m³ / min</u>	ft^3 / min	%	°⁄0	
		Below 0.5	Below 17.6	+/- 7	+/- 8	
		0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+,
30.1		1.5 to 15 Above 15	53 to 529.7 Above 529.7	+/- 5 +/- 4	+/- 6 +/- 5	