I			Rotary Compressor: Fixed S			_
	MODEL DATA - FOR COMPRESSED AIR					
	1	Manufacturer: ELGi	irer: ELGi			
	Model Number: EG 75-150		Date:	12/20/2022	_	
	2	X Air-cooled Water-cooled		Type:	SCREW	
				# of Stages:	1	
	3*	Rated Capacity at Full Loa	d Operating Pressure <sup>a, e</sup>	425	acfm <sup>a,e</sup>	
	4*		Load Operating Pressure <sup>b</sup> mum Full Flow Operating Pressure <sup>c</sup>		psig <sup>b</sup>	
	5					
	6	Drive Motor Nominal Rating		165	hp	
		Drive Motor Nominal Effic	-		· ·	-
	7			95.4	percent	_
	8	Fan Motor Nominal Rating (if applicable)		2.07(1.55)- (460V) X 1 Fans hp		_
	9	Fan Motor Nominal Efficie	-	NA 20.00	percent	_
	10*		kage Input Power at Zero Flow <sup>e</sup>		kW <sup>e</sup>	
	11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure <sup>d</sup>		86.28	$kW^d$	
	12*	Package Specific Power at Rated Capacity and Full Load Operating Pressure <sup>e</sup>			kW/100 cfm <sup>e</sup>	
	12*			20.30		
	13	Isentropic Efficiency		81.48	Percent	
I	*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator. Consult CAGI website for a list of participants in the third party verification program: <u>www.cagi.org</u>					
ressed Air & G	notes	<ul> <li>a. Measured at the discha ISO 1217, Annex C; A</li> <li>b. The operating pressure for this data sheet.</li> <li>c. Maximum pressure atta maximum pressure atta d. Total package input po e. Tolerance is specified i</li> </ul>	rge terminal point of the compressor package in accc CFM is actual cubic feet per minute at inlet conditio at which the Capacity (Item 3) and Electrical Consu- tinable at full flow, usually the unload pressure settii inable before capacity control begins. May require wer at other than reported operating points will vary n ISO 1217, Annex C, as shown in table below: wer" and "energy" are synonymous for purposes of t	ordance with ns. imption (Item 11) were measu ng for load/no load control or additional power. with control strategy.		
The second		Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Po
Member		<u>m<sup>3</sup>/min</u>	$\underline{ft^3 / min}$	%	0%	
		Below 0.5	Below 17.6	+/- 7	+/- 8	
		0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/-
030.1		1.5 to 15 Above 15	53 to 529.7 Above 529.7	+/- 5 +/- 4	+/- 6 +/- 5	