

COMPRESSOR DATA SHEET



In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: ELGi		
2	Model Number: EG 160SP 150 V		Date: 10/25/2024
	☒ Air-cooled ☐ Water-cooled	Type:	SCREW
	# of Stages: 2		
3*	Full Load Operating Pressure ^b	150	psig ^b
4	Drive Motor Nominal Rating	200	hp
5	Drive Motor Nominal Efficiency	96.2	percent
6	Fan Motor Nominal Rating (if applicable)	2.1 X 2	hp
7	Fan Motor Nominal Efficiency	NA	percent
8*	Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d
	172.4	900.0	19.15
	144.3	748.8	19.27
	130.3	668.9	19.48
	116.2	588.0	19.77
	101.8	505.0	20.15
	79.6	360.0	22.11
9*	Total Package Input Power at Zero Flow ^{c, d}	0.00	kW
10	Isentropic Efficiency	82.45	%
11	Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity		

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator



Website for a list of participants in the third party verification program: www.cagi.org

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	+/- 10%

ROT 031.1